

## In the Claims

1. (Cancelled).
2. (Cancelled).
3. (Cancelled).
4. (Cancelled).
5. (Cancelled).
6. (Cancelled).
7. (Cancelled).
8. (Cancelled).
9. (Cancelled).
10. (Cancelled).
11. (Cancelled).
12. (Cancelled).
13. (Cancelled).
14. (Cancelled).
15. (Cancelled).
16. (Cancelled).
17. (Cancelled).
18. (Cancelled).
19. (Cancelled).
20. (Cancelled).
21. (Cancelled).
22. (Cancelled).
23. (Cancelled).
24. (Cancelled).
25. (Cancelled).
26. (Cancelled).
27. (Cancelled).
28. (Cancelled).
29. (Cancelled).
30. (Cancelled).
31. (Cancelled).
32. (Cancelled).
33. (Cancelled).
34. (Cancelled).
35. (Cancelled).
36. (Cancelled).
37. (Cancelled).
38. (Cancelled).
39. (Cancelled).
40. (Cancelled).
41. (Cancelled).
42. (Cancelled).
43. (Cancelled).
44. (Cancelled).

- 45. (Cancelled).
- 46. (Cancelled).
- 47. (Cancelled).
- 48. (Cancelled).
- 49. (Cancelled).

50. (New) A method for secured software patching and upgrade in a distributed wireless sensor network, which comprises:

- receiving a software upgrade with a root node;
- communicating the software upgrade from the root node to a nodes acting as software upgrade repositories; and
- communicating a session key, a patch key length, and a prime modulus to the nodes acting as software upgrade repositories, causing the nodes to generate a patch key with the session key, patch key length, prime modulus, a Diffie-Hellman algorithm, and a locally-generated random number, the patch key being used by the nodes to authenticate a software upgrade.

51. (New) The method according to claim 50, wherein the patch key length varies based on a branch of a spanning-tree.

52. (New) The method according to claim 50, wherein the root node acts as a gateway to another network.

53. (New) The method according to claim 50, wherein the root node acts as a gateway to the Internet.

54. (New) The method according to claim 50, wherein the nodes acting as software upgrade repositories exist on orthogonal branches of the network.

55. (New) A method for secured software patching and upgrade in a distributed wireless sensor network, which comprises:

- receiving a software upgrade from a root node;
- receive a session key, a patch key length, and a prime modulus from the root node;
- generating a patch key with a Diffie-Hellman algorithm and a locally-generated random number, the patch key being used by the nodes to authenticate the software upgrade;

upgrading the software when authenticated prior to expiration of the session key.

56. (New) The method according to claim 55, wherein the patch key length varies based on a branch of a spanning-tree.

57. (New) The method according to claim 55, wherein the root node acts as a gateway to another network.

58. (New) The method according to claim 55, wherein the root node acts as a gateway to the Internet.